



LASER AND THERMAL CAMERAS

METRICA FLASH 100 METERS TARGET CAMERA



DETAILS

- $\circ\,$ Target camera, camera with viewfinder to see where you are measuring
- Double inclinometer (horizontal and vertical)
- Electronic vial
- Continuous measurement function, with max / min values always displayed
- Six Pythagoras functions
- Guided tracking
- Distances, surfaces, volumes
- Sum and subtraction of distances, surfaces and volumes
- Extractable end piece for diagonal measurement
- Measuring timer, auto shut off
- Sound function
- 100 memories
- PC Connection/Charging Cable
- Rechargeable batteries
- ∘ 1/4" tripod thread
- With strap, in box

TECHNICAL DATA SHEET

| | - | |
|----------------------------|----------------------------|--|
| PARAMETER | VALUE | |
| Range * | 100 m | |
| Accuracy | + / - 20 mm | |
| Angle measure | ± 90° | |
| Battery life | 30.000 single measurements | |
| Laser type | 635 nm | |
| Laser power | classe II | |
| Dust/Waterproofing | IP 54 | |
| Working temperature | 0° C / 40° C | |
| Batteries | NiMh 3X1.2V 800mAh | |
| Dimensions (mm) | 130 x 56 x 29 | |
| Weight (without batteries) | 130 g | |
| Tripod thread | 1/4" | |
| | | |

ARTICLES OF THE RANGE

| Ref. | | L | * |
|-------|---------------|--------------|---|
| 61186 | 8001066611867 | 0,05 ÷ 100 m | 1 |

GALLERY













