



LASER AND THERMAL CAMERAS

AUTOLIVELLO BRAVO LASER ROTATIVO H4



DETAILS


- Automatic laser level with visible rotating red beam: generates a horizontal self-leveled plane and the plomb line
- Dust/Waterproofing IP 66 resists completely to dust.
 Water protection: protected against water splashing from any direction
- SCANNER function to draw a more visible and shorter line with 4 different lengths
- SLOPE Function
- · MANUAL function that excludes automatic leveling and allows to tilt the device for tracing inclined planes
- TILT function: in case of accidentally moving the unit, the beam stops
- 4 rubber handles for easy and effective grip
- Remote control receiving on 4 sides of the unit

TECHNICAL DATA SHEET

PARAMETER	VALUE
Leveling accuracy H.	± 3 mm / 30 m
Self-leveling range	±5°
Autonomy	30 hour
Working range	diam 500 m (depending on weather conditions)
Rotational speeds	0-60-120-300-600 rpm
Scanner function	0° - 10° - 45° - 90° - 180°
Tilt function	si
Laser type	635 nm, 1mW
Laser output	Class 2
Power supply	4 x NiMH C4000mAh 1,2 V rechargeables
Dimensions	220 x 220 x 210 mm
Operating temperature	-10 °C / +50 °C
Weight (without batteries)	3,5 kg
Impermeability	IP 66

PARAMETER	VALUE
Tripod thread	5/8"
Remote control distance	30 / 10 m (in/out)
Batteries for remote control	2 x 15 V DC
Battery for the receiver	1 x 9 V DC

ARTICLES OF THE RANGE



GALLERY



