

LASER AND THERMAL CAMERAS

BRAVO LASER ROTATIVO HV4



DETAILS

- Automatic laser level with rotating red beam: generates a self-leveled horizontal or vertical plane and the plumb line
- High-sensitivity 4-line receiver
- Metal cover
- IP 66 dust/impermeability: protected against ingress of dust and water
- By rotating the unit 90°, the unit generates a vertical self-leveled laser plane and two horizontal beams
- SCANNER function to project a more visible and shorter line (adjustable to 4 lengths)
- SLOPE function (manual inclinations X, Y)
- MANUAL function, which excludes automatic levelling and allows the unit to be tilted at will
- TILT function: In case of unintentional movement the device switches off the laser beam.
- Laser with 4 rubberized handles for easier grip and increased protection
- Receiving the remote control on the 4 sides of the unit
- Rechargeable batteries and charger included or alternatively 4 alkaline batteries 1.5 V LR14

TECHNICAL DATA SHEET

PARAMETER	VALUE
Leveling accuracy	Horizontal ± 1 mm / 10 m Vertical ± 5 mm / 30 m
Self-leveling range	$\pm 5^\circ$
Operating time	~ 40 hours
Working range	500 m Ø (with receiver), depending on climatic conditions
Rotational speed	0 - 60 - 120 - 300 - 600 rpm
Scanner function	10° - 45° - 90° - 180°
Tilt function	Yes
Out-of-level warning	Yes
Laser type	635 nm, < 1 mW
Laser class	Class II
Rechargeable batteries	4 x C4000 Li-Ion

PARAMETER	VALUE
Dimensions	220 x 220 x 210 mm
Weight (without batteries)	3.5 kg
Operating temperature	-10 °C / +50 °C
Protection rating	IP66
Tripod thread	5/8"
Remote control range	~ 10 / 30 m (indoor/outdoor)
Remote control batteries	2 x 1.5 V DC
Receiver battery	1 x 9 V DC

ARTICLES OF THE RANGE

Ref.		
61350	8001066613502	1

GALLERY

