



LASER AND THERMAL CAMERAS

GROUND 360



DETAILS

- Green laser level. Projects: a horizontal plane over 360° plus a vertical plane at 90° to form 1 wall cross.
- Easy ceiling positioning (
- Laser with adjustable intensity
- Indoor/outdoor use (with receiver not included Code 60749)
- Automatic flashing of the laser if the device is out of the self-leveling range
- Automatic locking system to avoid vibrations during transport
- Compact design, non-slip and shockproof rubber coating
- ∘ ¼" connection for the tripod
- Magnetic base and metal cap for easy stacking
- Ion-Li batteries rechargeable via USB cable supplied

TECHNICAL DATA SHEET

| PARAMETER | VALUE |
|--|---------------------|
| Capacity (depending on ambient brightness) | 30 m (Ø 60 m) |
| Capacity with receiver | 50 m (Ø 100 m) |
| Leveling accuracy | ± 3 mm / 10 m |
| Self-leveling range | ± 4° |
| Signal out self-leveling | yes |
| Laser type | 505-550 nm < 1mw |
| Laser power | Classe II |
| Rechargeable batteries | 3,7 4400 mAh li-ion |
| Dimensions (mm) | 104 x 83 x 83 |
| Weight | 0,450 Kg |
| Dust/Waterproofing | IP 54 |
| Tripod thread | 1/4" |
| | |

ARTICLES OF THE RANGE



61425

80010666143257

-

GALLERY







