

LASER AND THERMAL CAMERAS

BRAVO LASER ROTATIVO INCLIGRAD 2 GREEN



DETAILS

- Creates a horizontal, vertical or inclined plane that can be adjusted by $\pm 10\%$ in X and Y direction and two plumb lines
- High-sensitivity receiver with deviation indication in mm
- Metal cover
- By rotating the unit 90° , the unit generates a vertical self-leveled laser plane and two horizontal beams
- Adjustment of the inclined plane shown on the display
- SCANNER function to project a more visible and shorter line (adjustable to 4 lengths: $10^\circ - 45^\circ - 90^\circ - 90^\circ - 180^\circ$)
- TILT function: In case of unintentional movement the device switches off the laser beam.
- Step-by-step rotation function
- MANUAL function which excludes automatic levelling
- Laser with 4 rubberized handles for easier grip and increased protection
- Remote control reception on the 4 sides of the unit for adjusting the X and Y axis inclinations
- Li-ion rechargeable battery.

TECHNICAL DATA SHEET

PARAMETER	VALUE
Leveling accuracy	horizontal ± 3 mm / 30 m
Leveling accuracy	vertical ± 5 mm / 30 m
Self-leveling range	$\pm 5^\circ$
Slopes of setting range	$\pm 10\%$
Self-leveling range	Quick electronic sensor
Autonomy	~ 35 hour
Working range	500 m \varnothing
Rotational speeds	0-60-120-300-600 rpm
Scanner function	$10^\circ - 45^\circ - 90^\circ - 180^\circ$
Tilt function	yes
Laser type	515/638nm,
Laser output	Class 2

PARAMETER	VALUE
Power supply	4 x Li-ion 4000mAh 1,2 V
Dimensions	220 x 220 x 210
Operating temperature	-10 °C / +50 °C
Weight (without batteries)	3,5 Kg
Impermeability	IP 54
Tripod thread	5/8"
Remote control distance	~ 30 / 10 m (in/out)
Batteries for remote control	2 x 1,5 V DC
Battery for the receiver	1 x 9 V DC

ARTICLES OF THE RANGE

Ref.		
61392	800106661392	1

GALLERY

