

LASER AND THERMAL CAMERAS

METRICA 4D



DETAILS

- Green self-leveling laser. Projects 4 laser planes at 360°: two horizontal planes and two vertical planes at 90 ° to each other
- Possibility to lock laser beams for inclined positions
- Possibility to lock laser beams for inclined positions
- Plumb line always visible with 4 squares at the walls
- 2 crosses, one at the ceiling and on the ground external to the base of the structure
- Optical glasses
- High visibility
- Easy ceiling positioning (< 2 cm)
- Easy ceiling positioning (< 2 cm)
- Indoor and outdoor use (with receiver not included)
- Automatic laser flashing and audible warning if the device is outside the self-leveling range
- Integrated locking system to prevent vibration during transport, possibility of projecting laser also with a fixed inclined position
- Compact, non-slip rubber bumper
- Li-ion rechargeable battery plus a spare battery and external charger
- USB-C port integrated in the instrument
- LED battery charge indicator
- Remote control (ref. 61465)
- Supplied with magnetic holder for plasterboard in a hard case

TECHNICAL DATA SHEET

PARAMETER	VALUE
Capacity (depending on ambient brightness)	30 m (Ø 60 m)
Working range with receiver	50 m (Ø 100 m)
Leveling accuracy	± 2 mm / 10 m
Self-leveling range	± 4°
Signal out self-leveling	yes
Laser type	520 nm <1mw
Laser power	Class II
Batteries	7.4V 2600 mAh

PARAMETER	VALUE
Dimensions	140 x 160 x 85
Weight (without batteries)	0,65 Kg
Dust/Waterproofing	IP 54
Tripod thread	1/4" - 5/8"

ARTICLES OF THE RANGE

Ref.  

61470 8001066614707 1

GALLERY

