

LASER AND THERMAL CAMERAS

DOUBLE LASER INCLIGRAD 2 - 30+20 M



DETAILS

- 50 m range (internal): 30 m (front) + 20 m (rear)
- Possibility of selecting front or rear beam only
- Aluminium body
- Horizontal/vertical inclinometer and 0° and 90° indicator
- Screen rotation
- Room Painter function
- Accuracy ± 2 mm unidirectional
- 5 Pythagorean functions
- Built-in rechargeable battery, USB-C

TECHNICAL DATA SHEET

PARAMETER	VALUE
Range *	0,05-30m (unidirectional internal) 50m (bidirectional internal)
Accuracy	± 2 mm
Angular measuring range	$\pm 90^\circ$
Laser class	Class II
Impermeability	IP 54
Laser type	630-670nm, <1mW
Automatic diode switch-off	20s
Device switches off after	180s
Battery life	8000 measurements
Beep	yes
Storage temperature	-20°C~60°C
Operating temperature	0°C~40°C
Maximum humidity	20%~80% RH
Batteries	Li-Ion 3,7V 850mAh
Dimensions	115x50x24.5mm

PARAMETER	VALUE
Weight	135 g

* according to ambient brightness

ARTICLES OF THE RANGE

Ref.	L		
61115	0,05 - 50 m	8001066611157	1

GALLERY

